


Accessories

Solis Export Power Manager

Solis Export Power Manager



The control center for smart energy management

The Solis export power manager is the ideal solution for smart energy management for both residential and commercial systems. The unit allows you to adjust export values to satisfy local network regulatory requirements.

Energy management with the Solis export power manager allows for higher self-consumption and efficient use of the locally generated PV power.

Easy to Use

- ▶ Active power limitation and control at the grid-connection point
- ▶ Automatic, intelligent control of loads with up to **80** Ginlong inverters
- ▶ Easy commissioning with the PV System Setup Assistant
- ▶ Ginlong monitoring system

Flexible

- ▶ Several standardised meter interfaces
- ▶ Individual specifications for controllable appliances



Datasheet

Model Name	Solis-EPM1-5G	Solis-EPM3-5G	Solis-EPM3-5G-PLUS
------------	---------------	---------------	--------------------

Communication

Inverter communication	RS485		
Monitoring	WiFi/GPRS		

Connections

Inverter connection	Single phase Ginlong inverters	Three phase Ginlong inverters	
Max. inverter number	10	80	
Monitoring connection	Wifi stick or GPRS stick for single inverter connection Wifi box or GPRS box for 2-6 inverter connection		Wifi box or GPRS box (Built-in)
Grid connection	L/N/PE	3L/(N)+PE	3L/N+PE

CT specification

CT connection	Plug terminal		
Recommended CT Input current range	100A standard	600A standard	300A/500A/1000A/1500A/2000A/3000A (optional)
CT Ratio	3000:1		3000:5

Max. range for communication

Totally RS485 cable length	1000 m
Standard CT cable length	10 m

Voltage supply

Voltage supply	Grid	
Input voltage	L to N: 100~ 277 Vac, 50 / 60 Hz	
Power consumption	<5W	<10W

Ambient conditions during operation

Ambient temperature	-25°C to +60°C
Degree of protection (according to EN IEC 60529)	IP65
Maximum permissible value for relative humidity (non-condensing)	5 % to 95 %

General data

Dimensions (W / H / D)	364*276*114mm	488*445.8*149mm
Weight	2.1kg	5.35kg
Mounting location	Indoor and outdoor	
Deployment options	Wall mounting	

Features

Operation	Via LCD
Warranty	5 years
Fail safe function and control time	Yes, 5 s
Accuracy	0.03
Remote upgrade	Support